

TR 600E

TROWEL ELECTRIC



For floating and trowelling freshly laid concrete floors.

All of our machines are versatile and easy to operate. Designed for heavy-duty applications and with high reliability. This means low running and maintenance costs.

- Reliable worm gearbox with permanent lubrication.
- Safe electric drive, environmentally friendly and silent.

- Long and height-adjustable handle.
- A folding handle makes transport and storage easy.
- Very low level of hand/arm vibrations.
- "Easy grip" dead-man's handle that is easy to hold from any point along the ergonomic handle.
- Strong protection frame with a lifting hook.
- The rotating protection ring offers excellent visibility features. An O-ring fitted on the out side of the cover protects walls against damage.
- All steel parts have been galvanized with an extra thick layer to provide better protection against corrosion.
- Screw or alternatively quick-pitch system for blade adjustment.
- Unique blade change system. Just one quick-release pin per blade.
- Accessory: Transport wheels.

TECHNICAL DATA – SWEPAC TR 600E	
Motor, electric	230V, 1-phase, 50 Hz
Motor power	1.5 kW
Speed RPM (motor)	2 810 rpm
Speed RPM (worm gear drive shaft)	130 rpm
Weight	
Weight Transport wheels (including fixture)	63 kg
Dimensions	
Protection ring diameter	2.6 kg
Trowel diameter	600 mm

TECHNICAL DATA – SWEPAC TR 600E	
Floating disc diameter	581 mm
Length in working position	595 mm
Height in working position	Approx 1 640 mm
Height in transport position	1 460 mm
Hand/arm vibrations (HAV) as per	980 mm
ISO 5349 on fresh concrete (using floating disc)	1.4 m/s ²
Guaranteed sound power level, LwA	93 dB(A)
Sound pressure level (at operator's level), OP	70 dB(A)
(at operator's level), OP	

TR600E_2021-05_GB