

TR 600P

TROWEL PETROL



For floating and trowelling freshly laid concrete floors.

All of our machines are versatile and easy to operate. Designed for heavy-duty applications and with high reliability. This means low running and maintenance costs.

- Reliable worm gearbox with permanent lubrication.
- Long and height-adjustable handle.

- A folding handle makes transport and storage easy.
- "Easy grip" dead-man's handle that is easy to hold from any point along the ergonomic handle.
- Strong protection frame with a lifting hook.
- Fast working speed reduces working time.
- The rotating protection ring offers excellent visibility eatures. An O-ring fitted on the outside of the cover protects walls against damage.
- All steel parts have been galvanized to provide better protection against corrosion.
- Screw or alternatively quick-pitch system for blade adjustment.
- Unique fast blade change system. Just one quickrelease pin per blade.
- Accessory: Transport wheels.
- Easy to service, change blades or floating disc
 just tilt the machine backwards with the transport wheels fitted.
- The machine has been designed such that when the machine is tilted backwards, no engine oil can escape through the valve into the carburettor or the silencer.

TECHNICAL DATA – SWEPAC TR 600P		
Engine	Honda GX160	
Engine output, max	3.6 kW (4.8 HP)	
Speed RPM (engine)	3 600 rpm	
Speed (worm gear drive shaft)	50-150 rpm	
Fuel tank capacity	3.1 liter	
Weight	65 kg	
Weight, rransport wheels weight (including fixture)	2.6 kg	
Dimensions		
Protection ring diameter	600 mm	
Trowel diameter	581 mm	

TECHNICAL DATA – SWEPAC TR 600P		
Floating disc diamete	er	595 mm
Length in working po	sition	Approx 1 640 mm
Height in working po	sition	980 mm
Height in transport p	osition	870 mm
Hand/arm vibrations per ISO 5349 on fres (using floating disc		4.4 m/s²
Guaranteed sound p LwA	ower level,	98 dB(A)
Sound pressure level (at operator's ear), O		85 dB(A)

R600P 2021-0F