

TR 950E

TROWEL ELECTRIC



For floating and trowelling freshly laid concrete floors.

All of our machines are versatile and easy to operate. Designed for heavy-duty applications and with high reliability. This means low running and maintenance costs.

- Safe electric drive, environmentally friendly and silent.
- · Long and height-adjustable handle.

- A folding handle makes transport and storage easy.
- Very low level of hand/arm vibrations.
- "Easy grip" dead-man's handle that is easy to hold from any point along the ergonomic handle.
- Lifting hook with integrated plate to protect the engine and the electrical fittings.
- Stepless speed settings with "soft-start" so that the machine starts gently and the speed increases from zero up to the speed setting.
- Very stable protection ring with excellent visibility features.
- All steel parts have been galvanized to provide better protection against corrosion.
- Screw or alternatively quick-pitch system for blade adjustment.
- Unique blade change system. Just one quick- release pin per blade.
- The electrical motor is mounted on a flat base-plate in the same way as the petrol version.
- Accessory: Transport wheels.

TECHNICAL DATA – SWEPAC TR 950E		
Motor, electric	400V, 3-phase, 50 Hz	
Motor power	2.5 kW	
Speed RPM (motor)	850-2 840 rpm	
Speed RPM (worm gear drive shafe	ft) 40–130 rpm	
Weight	84 kg	
Weight, transport wheels (including	ng fixture) 3 kg	
Dimensions		
Protective cover diameter	950 mm	
Trowel diameter	935 mm	

TECHNICAL DATA – SWEPAC TR 950E	
Floating disc diameter	945 mm
Length in working position	Approx 2 320 mm
Height in working position	1 065 mm
Height in transport position,	1 242 mm
Hand/arm vibrations (HAV) as per ISO 5349 on fresh concrete (using floating disc)	1.3 m/s ²
Guaranteed sound power level, LwA	98 dB(A)
Sound pressure level (at operator's ear), OP	72 dB(A)

TR950E_2021-05_GB