

TR 950P

TROWEL PETROL



For floating and trowelling freshly laid concrete floors.

All of our machines are versatile and easy to operate. Designed for heavy-duty and with high reliability. This means low running and maintenance costs.

- Reliable worm gearbox with permanent lubrication.
- Long and height adjustable handle.

- The handle can be folded to make transport and storage easy.
- "Easy grip" dead-man's handle that is easy to hold from any point along the ergonomic handle.
- Strong protection frame with a lifting hook.
- Fast working speed reduces the working time
- The strong protection ring offers excellent visibility features.
- All steel parts have been galvanized to provide better protection against corrosion.
- Screw or alternatively quick-pitch system for blade adjustment.
- Unique fast blade change system. Just one quick-release pin per blade .
- Accessory: Transport wheels.
- Easy to service, change blades or levelling disc just tilt the machine backwards with the transport wheels fitted.
- The machine has been designed such that when the machine is tilted backwards, no engine oil can escape through the valve into the carburettor or the silencer.

TECHNICAL DATA – SWEPAC TR 950P	
ngine, petrol	Honda GX200 alt, GX270
Engine powe	4.3 kW (5.8 HP) alt, 6.3 kW (8.4 HP)
Speed RPM (engine)	3 600 rpm
Speed RPM (drive shaft)	Stepless, 50–150 rpm
Fuel tank capacity	3.1 alt, 5.3 liter
Weight	96 kg
Weight, transport wheels (including fixture)	Approx 3 kg
Dimensions	
Protective cover diameter	950 mm

TECHNICAL DATA – SWEPAC TR 950P	
Trowel diameter	935 mm
Floating disc diameter	945 mm
Length in working position	2 325 mm
Height in working position	1 065 mm
Height in transport position	1 242 mm
Hand/arm vibrations (HAV) as per ISO 5349 on fresh concrete (using floating disc)	4.3 m/s² (GX200) 4.2 m/s² (GX270)
Guaranteed sound power level, LwA	105 dB(A)
Sound pressure level (at operator's ear), OP	92 dB(A)

R950P_2021-09