

TR 950STD TROWEL PETROL



For floating and trowelling freshly laid concrete floors.

All of our machines are versatile and easy to operate. Designed for heavy-duty applications and with high reliability. This means low running and maintenance costs.

- Reliable worm gearbox with permanent lubrication.
- Forward folding handle makes transport and storage easy.
- Handle-grip adjustable in different heights.

- Light dead-man's handle that is easy to hold and designed for quick stop.
- Strong lifting hook, easy to use with fork or strap.
- Fast working speed reduces the working
- The strong rotating protection ring offers excellent visibility features.
- All steel parts are powder coated for strong protection against corrosion.
- Screw pitch system for blade adjustment.
- Unique fast blade change system. Just one quick- release pin per blade.
- Accessory: Transport wheels.
- · Easy to service, change blades or floating disc – just tilt the machine backwards on the advised support.
- The machine has been designed such that when the machine is tilted backwards no engine oil can escape through the valve into the carburettor or the silencer.

TECHNICAL DATA – SWEPAC TR 950STD	
Engine, petrol	Honda GX200
Engine power	4.3 kW (5.8 HP)
Speed RPM (engine)	3 600 rpm
Speed RPM (drive shaft)	Stepless, 75-150 rpm
Fuel tank capacity	3.1
Weight excl transport wheels	81.5 kg
Weight, transport wheels (including fixture)	Approx 3 kg
Dimensions	
Protective cover diameter	951 mm
Trowel diameter	935 mm

TECHNICAL DATA – SWEPAC TR 950STD	
Floating disc diameter	945 mm
Length in working position	1 770 mm
Handle height in working position	965 mm
Height in transport position	785.5 mm
Hand/arm vibrations (HAV) as per ISO 5349 on fresh concrete (using floating disc)	6.5 m/s ²
Guaranteed sound power level, LwA	105 dB(A)
Sound pressure level (at operator's ear), OP	92 dB(A)